

# SMD TCXO

## Crystal Oscillators

### 1.6x1.2x0.6mm W16 Series



#### Features


- Temperature Stability:  $\pm 0.5 \text{ ppm} \sim \pm 2.0 \text{ ppm}$ .
- Operating Temperature Range:  $-30^\circ\text{C} \sim 85^\circ\text{C}$ .
- Supply Voltage: 1.8V~3.3V.
- Voltage Control Function Available.
- Applications: GPS, WiMAX, Cellular and Wireless Communications.
- RoHS Compliant / Pb Free.



#### Crystals specifications

ITEMS/TYPE		W16
Frequency Range		26~52MHz
Output Load		10KΩ // 10pF
Oscillation Mode		Fundamental
Supply Voltage		1.8~3.3 V
Output Type		Clipped Sinewave
Clipped Sinewave Output Voltage		0.8 Vp-p min
Supply Current		2.0mA max.
Harmonics		- 5 dBc Max.
Output Level		0.8 Vp-p min
Frequency Stability	Vs Temperature( $-30 \sim +85^\circ\text{C}$ )	$\pm 0.5 \text{ ppm} / \pm 2.0 \text{ ppm}$
	Supply Voltage ( $V_{cc} = \text{Typical } \pm 0.1 \text{ V}$ )	$\pm 0.2 \text{ ppm max.}$
	Load ( Load varies $\pm 10\%$ )	$\pm 0.2 \text{ ppm max. (10K}\Omega / 10\text{pF}\pm 10\%)$
Slope of Frequency Drift		$\pm 0.1 \text{ ppm} / ^\circ\text{C}$ Typical ; $\pm 0.5 \text{ ppm} / ^\circ\text{C}$ Max.
Initial Frequency Tolerance at $25^\circ\text{C}$ after 2 Reflows		$\pm 2.5 \text{ ppm max. (After 2 times reflow)}$
Storage Temperature Range		- 40~ $+85^\circ\text{C}$
Auto Frequency Control Range		$\pm 7 \sim \pm 16 \text{ ppm (1.4+/- 1V)}$
Start-up Time		5 ms max.
Phase Noise at 1 kHz offset		- 130 dBc / Hz
Aging(at $25^\circ\text{C}$ )		$\pm 1 \text{ ppm / year}$
Packing Unit		3,000pcs/Reel

#### Dimensions and patterns(unit:mm)




Pin Connection

Name	Connection
Pin 1	AFC or GND
Pin 2	GND
Pin 3	OUTPUT
Pin 4	VCC



Recommended Land Pattern



Units:mm